
DALI2 multi address controller || 12 ~ 36V | 5*5A | DT6/DT8

ARTICLE NUMBER: 214-190

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

Advanced 5-channel DALI controller for RGBTW, RGBW, RGB, tuneable white and single-colour LED lighting. Supports DALI DT6/DT8 and PushDim. Compatible with 12–36V DC systems, with up to 5 A per output.

Key product features

- **Type of control:** DALI
- **Number of colour channels:** 5
- **Output voltage (V):** 12 – 36
- **Input voltage (V):** 12 – 36
- **Max. output current (A):** 5
- **Control type:** Constant voltage
- **Number of zones:** 5


Technical specifications:

Product Name	DALI2 multi address controller || 12 ~ 36V | 5*5A | DT6/DT8
Ean	8714984947818
Outer box qty	64st
Model	Dynamic
Housing	Plastic housing
Programmable	No
Max. output current	5A
Output voltage	12 - 36V
Suitable for outdoor use	No
Degree of protection (IP)	IP20
Length	170mm
Width	59mm
Height	29mm
Number of zones	5
Number of colour channels	5, RGBTW

17.11.2026 - Disclaimer: information subject to change.

Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Input voltage	12 - 36V
Control method	DALI
DIN-rail mounting	No
Brand	Tronix Lighting
Compatible with Casambi	No
Control type	Constant voltage
Warranty	5 years





17.11.2026 - Disclaimer: information subject to change.