
eldoLED ECOdrive | 12NA-E1ZLP | 350~700mA | 12W | TE dim.

ARTICLE NUMBER: 215-666

View this product in our webshop

eldoLED



17.11.2026 - Disclaimer: information subject to change.

Ultra-compact phase-cut dimmable LED driver for constant current applications. Silent, flicker-free dimming to 1% and easy current selection via dipswitch. Fits fixtures with limited space.

Key product features:

- **Suitable for constant current:** Yes
- **Output voltage (V):** 10 - 20
- **Output current (mA):** 350 - 700
- **Output power (W):** 3,5 - 12
- **Dimmig phase cut-off (trailing edge):** Yes
- **Dimmig phase cut-on (leading edge):** Yes

Technical specifications:

Product Name	eldoLED ECOdrive | 12NA-E1ZLP | 350~700mA | 12W | TE dim.
Ean	8714984950702
Outer box qty	75st
Housing	Plastic housing
Model	Static
Output voltage	10 - 20V
Output current	350 - 700mA
Suitable for outdoor use	No
Suitable for DC-voltage (primary side)	No
Output power	3.5 - 12W
Degree of protection (IP)	IP20
Length	128.8mm
Width	32mm
Height	42.6mm
Power consumption	14W
Input voltage	220 - 240V
Frequency input voltage	50 - 50Hz

17.11.2026 - Disclaimer: information subject to change.

Overload protection	Yes
Overtemperature protection	Yes
Control method	Trailing edge dimming
Short-circuit protected	Yes
Ambient temperature	-20 - 45??C
Driver lifetime	50000h
DIN-rail mounting	No
Brand	eldoLED
Dimmable	Yes
Emergency power supply system	None
Control type	Constant current
Warranty	5 years

17.11.2026 - Disclaimer: information subject to change.