TRONIX guided by light

eldoLED | LINEARdrive 211/D | 1CH | 2 out | 0-10V

ARTICLE NUMBER: 214-354

View this product in our webshop

eldoLED



17.11.2026 - Disclaimer: information subject to change.

Professional 0–10V LED controller (12–28V DC) with a single channel and dual output (total 8 A). Suitable for white light applications up to 200 W, offering precise, flicker-free dimming down to 0.1%.

Key product features

- **Number of colour channels:** 1
- **Output voltage (V):** 12 – 28
- **Input voltage (V):** 12 – 28
- **Max. output current (A):** 8
- **Control type:** Constant voltage
- **Type of control:** 0/1–10V
- **Number of zones:** 1

Technical specifications:

Product Name	eldoLED | LINEARdrive 211/D | 1CH | 2 out | 0-10V
Ean	8714984944268
Outer box qty	12st
Model	Dynamic
Housing	Plastic housing
Programmable	Yes
Max. output current	8A
Output voltage	12 - 28V
Suitable for outdoor use	No
Degree of protection (IP)	IP20
Length	153mm
Width	50mm
Height	23mm
Number of zones	1
Number of colour channels	1, Single Colour

17.11.2026 - Disclaimer: information subject to change.

Suitable for surface mounting	Yes
Suitable for built-in mounting	Yes
Input voltage	12 - 28V
Control method	0/1-10V
DIN-rail mounting	No
Brand	eldoLED
Compatible with Casambi	No
Control type	Constant voltage
Warranty	5 years

