TRONIX guided by light

eldoLED || LINEARdrive 220/D | 2CH | 2 out | DALI DT6

ARTICLE NUMBER: 214-355

View this product in our webshop

eldoLED



17.11.2026 - Disclaimer: information subject to change.

Professional 2-channel DALI LED controller (12–28V DC) with a maximum output power of 200 W. Supports Tuneable White and single-colour applications. Flicker-free dimming down to 0.1% via HydraDrive.

Key product features

- **Type of control:** DALI
- **Number of colour channels:** 2
- **Output voltage (V):** 12 – 28
- **Input voltage (V):** 12 – 28
- **Max. output current (A):** 8
- **Control type:** Constant voltage
- **Number of zones:** 4

Technical specifications:

Product Name	eldoLED || LINEARdrive 220/D | 2CH | 2 out | DALI DT6
Ean	8714984944527
Outer box qty	12st
Model	Dynamic
Housing	Plastic housing
Programmable	Yes
Max. output current	8A
Output voltage	12 - 28V
Suitable for outdoor use	No
Degree of protection (IP)	IP20
Length	153mm
Width	50mm
Height	23mm
Number of zones	2
Number of colour channels	2, Tuneable White

17.11.2026 - Disclaimer: information subject to change.

Suitable for surface mounting	Yes
Suitable for built-in mounting	Yes
Input voltage	12 - 28V
Control method	DALI
DIN-rail mounting	No
Brand	eldoLED
Compatible with Casambi	No
Control type	Constant voltage
Warranty	5 years

