Ground spot | 215mm | 40 watt | 30° | IP67 | RGBW | DMX512

ARTICLE NUMBER: 190-140

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

This RGBW LED ground spot offers high resistance to various weather conditions, making it ideally suited as lighting in a garden, along a sidewalk or next to a facade. The inside offers a tiltable frame, making it possible to direct the light as desired.

Features

- RGBW: Red, green, blue, warm white (3000K)
- DMX512 controllable
- Programmed on DMX channel 1 (other channels possible)

Our LED RGB fixtures collection

The collection of LED RGB fixtures offers plenty of possibilities in terms of powerful, colorful lighting for facades and properties. These wall washers feature powerful LED chips in a sturdy frame, which offers high resistance to UV rays and weather. These fixtures also work on the basis of DMX512, so that every project can be taken care of down to the last detail.

Technical specifications:

Product Name	Ground spot | 215mm | 40 watt | 30° | IP67 | RGBW | DMX512
Ean	8714984949034
Outer box qty	4st
Dimmable	Yes
Dimming DMX	Yes
Dimming phase cut-off (trailing edge)	No
Lamp type	LED not exchangeable
Lamp holder	None
Housing colour	Anthracite
Housing material	Aluminium
Material cover	Glass transparent
Connection type	Other


Built-in length	209mm
Built-in height/depth	209mm
Built-in diameter	203mm
Outer diameter	215mm
Colour of light	RGBW
Colour temperature	RGBW
Colour rendering index CRI	80-89
Colour of light adjustable	No
Luminous flux adjustable	No
Constant light output (CLO)	No
Beam angle	21-40° - Medium beam
Beam angle adjustable	No
Voltage type	DC
Nominal voltage	24 - 24V
Nominal current	- - -mA
Number of poles	3
Light source included	Yes, fixed LED
Light distributor	Reflector
Light distribution	Symmetric
Connectable conductor cross section	0.75 - 2.5mm²
Type of control gear	LED operating device current-controlled
With control gear	Yes
Exchangeable control gear	No
Max. surface temperature	50°C
Max. load	5kg
Over rollable	No
Housing material quality	Stainless steel 316 (1.4401)


17.11.2026 - Disclaimer: information subject to change.

Electrical connection with connector system	No
Adjustable	No
Degree of protection (IP)	IP67
Rated lifetime L70/B50 at 25 °C	50000h
Max. system power	40W
Rated luminous flux according to IEC 62722-2- 1	1600 - 1600lm
Luminaire efficacy	40lm/W
Impact strength	IK10
Power factor	0.9
Type of wiring	Ending
Warranty	5 years
Ambient temperature	-20 - 50°C









17.11.2026 - Disclaimer: information subject to change.