# Ground spot || 24V | 42mm | matt | grey ring | 2,4W | 3000K

ARTICLE NUMBER: 140-014

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

24V ground spot with high-quality stainless steel cover ring and CREE LEDs. Power supply excluded.

**Features**

IK08 and IP67
24V, excluding power supply
Extra long connection cable (3 meters)

**Technical specifications:**

| | |
|---|---|
| Product Name | Ground spot \|\| 24V \| 42mm \| matt \| grey ring \| 2,4W \| 3000K |
| Ean | 8714984925960 |
| Outer box qty | 20st |
| Dimmable | No |
| Dimming DMX | No |
| Dimming phase cut-off (trailing edge) | No |
| Lamp type | LED not exchangeable |
| Lamp holder | None |
| Housing colour | Anthracite |
| Housing material | Aluminium |
| Material cover | Glass matt/satinized |
| Connection type | Other |
| Length | 63mm |
| Height/depth | 63mm |
| Built-in length | 90mm |
| Built-in height/depth | 90mm |
| Built-in diameter | 39mm |
| Outer diameter | 42mm |
| Colour of light | White |
| Colour rendering index CRI | 80-89 |


17.11.2026 - Disclaimer: information subject to change.

| | |
|---|---|
| Colour of light adjustable | No |
| Luminous flux adjustable | No |
| Constant light output (CLO) | No |
| Beam angle | > 80° - Extreme wide beam |
| Beam angle adjustable | No |
| Voltage type | DC |
| Nominal voltage | 24 - 24V |
| Nominal current | 700 - 700mA |
| Number of poles | 2 |
| Light distributor | Diffuser lens/optic/panel |
| Light distribution | Symmetric |
| Connectable conductor cross section | 0.75 - 2.5mm² |
| Type of control gear | LED operating device voltage-controlled |
| With control gear | No |
| Exchangeable control gear | Yes |
| Max. surface temperature | 50°C |
| Max. load | 0.25kg |
| Over rollable | No |
| Housing material quality | Other |
| Electrical connection with connector system | No |
| Adjustable | No |
| Degree of protection (IP) | IP67 |
| Rated lifetime L70/B50 at 25 °C | 30000h |
| Max. system power | 2.4W |
| Rated luminous flux according to IEC 62722-2- 1 | 111 - 111lm |
| Luminaire efficacy | 46.3lm/W |

17.11.2026 - Disclaimer: information subject to change.

| | |
|---|---|
| Impact strength | IK08 |
| Type of wiring | Ending |
| Warranty | 3 years |
| Ambient temperature | -20 - 50°C |






17.11.2026 - Disclaimer: information subject to change.