TRONIX guided by light

# KNX actuator || 4CH x 5A | 12 ~ 36V

ARTICLE NUMBER: 214-191

View this product in our webshop




17.11.2026 - Disclaimer: information subject to change.

CARE SHARE CONNECT

tronixlighting.com

Powerful 4-channel KNX controller for constant voltage LEDs – ideal for RGB(W) applications or independently controlling four channels in smart building management systems. Fully compatible with any standard KNX setup.

### Key product features

- **Control type:** KNX
- **Output voltage (V):** 12 – 36
- **Input voltage (V):** 12 – 36
- **Max. output current (A):** 5

### Technical specifications:

| | |
|---|---|
| Product Name | KNX actuator \|\| 4CH x 5A \| 12 ~ 36V |
| Ean | 8714984951693 |
| Outer box qty | 1st |
| Model | Dynamic |
| Housing | Plastic housing |
| Programmable | Yes |
| Max. output current | 5A |
| Output voltage | 12 - 36V |
| Suitable for outdoor use | No |
| Degree of protection (IP) | IP20 |
| Length | 170mm |
| Width | 53.4mm |
| Height | 28mm |
| Number of zones | 4 |
| Number of colour channels | 4, RGBW |
| Suitable for surface mounting | Yes |
| Suitable for built-in mounting | Yes |

17.11.2026 - Disclaimer: information subject to change.

| | |
|---|---|
| Input voltage | 12 - 36V |
| Control method | KNX |
| DIN-rail mounting | No |
| Brand | Tronix Lighting |
| Compatible with Casambi | No |
| Control type | Constant voltage |
| Warranty | 5 years |