LED driver | eldoLED DUALdrive 20CA-E2Z0D | 20W | DALI DT6

ARTICLE NUMBER: 215-640

View this product in our webshop

eldoLED



17.11.2026 - Disclaimer: information subject to change.

Designed specifically for downlights, this eldoLED DUALdrive LED driver offers a unique combination of adjustable output current within a compact design. This ensures easy and safe installation, as you only need a 45 mm cutout.

Features

- Compact size for easy installation. The driver fits through openings of only 45 mm and even works in ceilings with only 100 mm space.
- Easy programming thanks to the LEDcode interface.
- Smooth dimming experience with tuneable white capabilities.

Technical specifications:

Product Name	LED driver | eldoLED DUALdrive 20CA-E2Z0D | 20W | DALI DT6
Ean	8714984949942
Outer box qty	50st
Housing	Plastic housing
Model	Static
Output voltage	2 - 40V
Output current	150 - 1050mA
Suitable for outdoor use	No
Suitable for DC-voltage (primary side)	Yes
Output power	20 - 20W
Degree of protection (IP)	IP20
Length	173.8mm
Width	40.35mm
Height	28.8mm
Power consumption	20W
Input voltage	220 - 240V
Frequency input voltage	- - -Hz

17.11.2026 - Disclaimer: information subject to change.


Overload protection	Yes
Overtemperature protection	Yes
Control method	DALI
Short-circuit protected	Yes
Ambient temperature	- - -??C
DIN-rail mounting	No
Brand	eldoLED
Dimmable	Yes
Emergency power supply system	None
Control type	Constant current
Warranty	5 years











17.11.2026 - Disclaimer: information subject to change.