TRONIX guided by light

LED driver | eldoLED SOLOdrive 560/A | 50W | DALI

ARTICLE NUMBER: 215-271

View this product in our webshop

eldoLED



17.11.2026 - Disclaimer: information subject to change.

The SOLOdrive LED drivers from eldoLED feature a programmable output (constant current) and offer the ability to dim down to 0.1%. Also easy to apply in combination with single color, dimmable LED fixtures on a DALI basis.

Features

- Can be combined with the 214-231 Casambi module (via the LED code input)
- Can be combined with a variety of LED lighting, including single color lighting on DALI
- Output current: 150 - 1400 mA
- Output voltage: 2 - 55 volts

Technical specifications:

Product Name	LED driver | eldoLED SOLOdrive 560/A | 50W | DALI
Ean	8714984942295
Outer box qty	40st
Housing	Plastic housing
Model	Static
Output voltage	2 - 55V
Output current	150 - 1400mA
Suitable for outdoor use	No
Suitable for DC-voltage (primary side)	Yes
Output power	0.3 - 50W
Degree of protection (IP)	IP20
Length	152.5mm
Width	76.2mm
Height	30.1mm
Power consumption	40W


17.11.2026 - Disclaimer: information subject to change.

Input voltage	120 - 250V
Frequency input voltage	- - -Hz
Overload protection	Yes
Overtemperature protection	Yes
Control method	DALI
Short-circuit protected	Yes
Ambient temperature	-20 - 50??C
Driver lifetime	50000h
Number of colour channels	1
DIN-rail mounting	No
Brand	eldoLED
Dimmable	Yes
Emergency power supply system	None
Control type	Constant current
Warranty	5 years

17.11.2026 - Disclaimer: information subject to change.






Mounting Center: 118 mm / 4.65 in
Width:
76.2 mm / 3 in
Mounting Center:
66.2 mm / 2.6 in
Height:
30.5 mm / 1.2 in
Mounting Center Hole Diameter:
5 mm / 0.2 in
Length: 153mm / 6 in