LED exit sign IP65 | surface mount | AT | incl. pictograms

ARTICLE NUMBER: 600-043

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

Impact-resistant and waterproof LED emergency light with automatic self-test, 240-lumen output, and a 30-metre viewing distance. Designed for ceiling mounting in indoor and outdoor areas. Supplied with 9 interchangeable pictograms.

Key product features

- **Mounting method:** Ceiling surface mounting
- **Max. system power (W):** 5
- **Degree of protection (IP):** IP65
- **Recognition distance (m):** 30
- **Function:** Escape route indication
- **Impact strength:** IK10
- **Emergency function monitoring system:** Automatic self-diagnosis

Technical specifications:

Product Name	LED exit sign IP65 | surface mount | AT | incl. pictograms
Ean	8714984946972
Outer box qty	6st
Housing material	Plastic
Lamp type	LED not exchangeable
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal current	80 - 80mA
Type of control gear	LED operating device current-controlled
Battery technology	Lithium-ion
Mounting method	Ceiling surface mounting
Degree of protection (IP)	IP65
Nominal voltage	220 - 240V

Length	194mm
Width	340mm
Height	108mm
Height/depth	108mm
Colour temperature	5000 - 5000K
Exchangeable control gear	No
Function	Escape route signage
With pictogram	Yes
Suitable for standby switching	Yes
Suitable for continuous circuit	Yes
Impact strength	IK10
RAL-number housing	9016
Connection type	Plug-in connection
Light distributor	Diffuser lens/optic/panel
Rated lifetime L70/B50 at 25 ??C	50000h
Luminous flux in standby mode	240lm
Nominal operation time	3 - 3h
Max. system power	5W
Power factor	0.3
Type of wiring	Ending
Number of poles	2
With heating element for battery	No
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Rated luminous flux according to IEC 62722-2- 1	240 - 240lm
Emergency power supply system	Peripheral (individual battery)
Emergency function monitoring system	Automatic self test


17.11.2026 - Disclaimer: information subject to change.


Recognition distance	30m
Power consumption in emergency mode	2W
Type of indicator	Single/double-sided
Connectable conductor cross section	0.75 - 2.5mm??
Suitable for labelling type	Insert sheet/plate
Warranty	5 years (battery 2 years)
Ambient temperature	1 - 45??C

17.11.2026 - Disclaimer: information subject to change.









17.11.2026 - Disclaimer: information subject to change.