TRONIX guided by light

LED exit sign | wall mount | white | AT | incl. pictograms

ARTICLE NUMBER: 600-019

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

Compact LED emergency luminaire with automatic self-test, orientation lighting and interchangeable pictograms. Suitable for wall mounting or semi-recessed installation. Ideal for permanent escape route indication in professional environments.

Key product features

- **Mounting method:** Surface/recessed
- **Max. system power (W):** 5
- **Housing colour:** White
- **Type of indicator:** Single-sided
- **Recognition distance (m):** 25
- **Function:** Escape route lighting/indication
- **Emergency function monitoring system:** Automatic self-diagnosis


Technical specifications:

Product Name	LED exit sign | wall mount | white | AT | incl. pictograms
Ean	8714984942349
Outer box qty	10st
Housing material	Plastic
Lamp type	LED not exchangeable
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal current	50 - 50mA
Type of control gear	LED operating device current-controlled
Battery technology	Lithium-ion
Mounting method	Surface mounting/recessed mounting
Degree of protection (IP)	IP40
Nominal voltage	220 - 240V

Length	330mm
Width	190mm
Height	45mm
Height/depth	45mm
Colour temperature	5000 - 5000K
Exchangeable control gear	No
Function	Escape route lighting/signage
With pictogram	Yes
Suitable for standby switching	Yes
Suitable for continuous circuit	Yes
Impact strength	IK07
RAL-number housing	9016
Connection type	Plug-in connection
Light distributor	None
Rated lifetime L70/B50 at 25 ??C	50000h
Luminous flux in standby mode	35lm
Nominal operation time	3 - 3h
Max. system power	1W
Power factor	0.3
Type of wiring	Ending
Number of poles	2
With heating element for battery	No
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Rated luminous flux according to IEC 62722-2- 1	35 - 35lm
Emergency power supply system	Peripheral (individual battery)
Emergency function monitoring system	Automatic self test


17.11.2026 - Disclaimer: information subject to change.


Luminous flux in emergency mode	50lm
Recognition distance	25m
Power consumption in emergency mode	1.5W
Type of indicator	Single-sided
Connectable conductor cross section	0.75 - 2.5mm??
Suitable for labelling type	Insert sheet/plate
Warranty	5 years (battery 2 years)
Ambient temperature	1 - 45??C














17.11.2026 - Disclaimer: information subject to change.