LED strip|| 24V | 120LED/m 3528 | 5m | IP67 | 2700K | CRI>90

ARTICLE NUMBER: 127-089

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

24V LED strip with 120 pcs 3528 LEDs per meter. Uniform light output, stable performance and versatile for professional applications.

Key product features:

- **Number of nodes per meter:** 120
- **Lamp power per meter (W):** 9.6
- **Colour temperature (K):** 2700
- **Width (mm):** 4
- **Length of particular sections (mm):** 50
- **Degree of protection (IP):** IP67
- **Luminous flux per meter (Lm):** 610


Technical specifications:


Product Name	LED strip|| 24V | 120LED/m 3528 | 5m | IP67 | 2700K | CRI>90
Ean	8714984927391
Outer box qty	25st
Model	Strip
Lamp type	LED not exchangeable
Lamp voltage	0 - 24V
Number of nodes per meter	120
Lamp power per meter	9.6W
Beam angle	120°
Voltage type	DC
Type of control gear	LED operating device voltage-controlled
Input voltage tracklights	24V
With protective cover	Yes
Length of particular segments	50mm
Degree of protection (IP)	IP67
Self-adhesive	Yes


Luminous flux per meter	652lm
Total length	5m
Width	10mm
Height/depth	4mm
Colour of light	White
Suitable for dimmer	Yes
Colour rendering index CRI	90-100
Exchangeable control gear	Yes
Connection type	Other
Rated lifetime L70/B50 at 25 °C	54000h
Colour of light adjustable	No
Luminous flux per foot	198.73lm
Luminous flux adjustable	Continuously variable
LED type	SMD
Max. system power	48W
Beam angle adjustable	No
Luminaire efficacy	68lm/W
Power factor	1
Type of wiring	Loop-through wiring included
Number of poles	2
Connectable conductor cross section	0.5 - 2.5mm²
Colour temperature	2700K
Warranty	3 years
Ambient temperature	-20 - 50°C
Lowest bending radius	50mm

17.11.2026 - Disclaimer: information subject to change.









17.11.2026 - Disclaimer: information subject to change.