TRONIX guided by light

LED strip || 24V | 60LED/m 3528 | 5m | IP67 | 2700K | CRI>90

ARTICLE NUMBER: 127-082

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

24V LED strip with 60 pcs 3528 SMD LEDs per meter. Based on stable technology, ideal for indirect lighting such as coves.

Key product features:

- **Number of nodes per meter:** 60
- **Lamp power per meter (W):** 4.8
- **Colour temperature (K):** 2700
- **Width (mm):** 10
- **Length of particular sections (mm):** 100
- **Degree of protection (IP):** IP67
- **Luminous flux per meter (Lm):** 278

Technical specifications:


Product Name	LED strip || 24V | 60LED/m 3528 | 5m | IP67 | 2700K | CRI>90
Ean	8714984931077
Model	Strip
Lamp type	LED not exchangeable
Lamp voltage	0 - 24V
Number of nodes per meter	60
Lamp power per meter	4.8W
Beam angle	120°
Voltage type	DC
Type of control gear	LED operating device voltage-controlled
Input voltage tracklights	24V
With protective cover	Yes
Length of particular segments	1000mm
Degree of protection (IP)	IP67
Self-adhesive	Yes
Luminous flux per meter	325lm


17.11.2026 - Disclaimer: information subject to change.

Total length	5m
Width	10mm
Height/depth	4mm
Colour of light	White
Suitable for dimmer	Yes
Colour rendering index CRI	90-100
Exchangeable control gear	Yes
Connection type	Other
Rated lifetime L70/B50 at 25 °C	54000h
Colour of light adjustable	No
Luminous flux per foot	99.06lm
Luminous flux adjustable	Continuously variable
LED type	SMD
Max. system power	24W
Beam angle adjustable	No
Luminaire efficacy	67lm/W
Power factor	1
Type of wiring	Loop-through wiring included
Number of poles	2
Connectable conductor cross section	0.5 - 2.5mm²
Colour temperature	2700K
Warranty	3 years
Ambient temperature	-20 - 50°C
Lowest bending radius	50mm

17.11.2026 - Disclaimer: information subject to change.







17.11.2026 - Disclaimer: information subject to change.