TRONIX guided by light

LED strip | COB 840LED/m | 15W/m | IP20 | RGB

ARTICLE NUMBER: 127-133

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

RGB COB LED strip with seamless light output and powerful colour rendering. Designed for custom lighting applications with 50 mm cutting sections and versatile control options.

Key product features

- **Lamp power per meter (W):** 15
- **Width (mm):** 10
- **Length of particular sections (mm):** 50
- **Degree of protection (IP):** IP20
- **Luminous flux per meter (Lm):** 645
- **Colour of light:** RGB

Technical specifications:

Product Name	LED strip | COB 840LED/m | 15W/m | IP20 | RGB
Ean	8714984940758
Outer box qty	25st
Model	Strip
Lamp type	LED not exchangeable
Lamp voltage	0 - 24V
Number of nodes per meter	840
Lamp power per meter	15W
Beam angle	180°
Voltage type	DC
Type of control gear	LED operating device voltage-controlled
Input voltage tracklights	24V
With protective cover	No
Length of particular segments	50mm
Degree of protection (IP)	IP20
Self-adhesive	Yes


17.11.2026 - Disclaimer: information subject to change.

Luminous flux per meter	640lm
Total length	5m
Width	10mm
Height/depth	2mm
Colour of light	RGB
Suitable for dimmer	Yes
Exchangeable control gear	Yes
Connection type	Other
Rated lifetime L70/B50 at 25 °C	54000h
Colour of light adjustable	Continuously variable
Luminous flux per foot	195.07lm
Luminous flux adjustable	Continuously variable
LED type	COB
Max. system power	75W
Beam angle adjustable	No
Luminaire efficacy	40lm/W
Power factor	1
Type of wiring	Loop-through wiring included
Number of poles	2
Connectable conductor cross section	0.5 - 2.5mm²
Colour temperature	RGB
Warranty	3 years
Ambient temperature	-20 - 50°C
Lowest bending radius	10mm

17.11.2026 - Disclaimer: information subject to change.






50 mm
10 mm