# Refl downl || white | Ø190mm | 60° | 3000K | 6~15W | EU plug

ARTICLE NUMBER: 136-350

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

This downlight offers aesthetics and functionality. Its adjustable output and wide beam angle of 60° ensure optimal light distribution. A glass in front of the reflector keeps out moisture and dust, ideal for situations requiring a robust solution.

**Key product features:**

- **Max. system power (W):** 6 – 15
- **Colour temperature (K):** 3000
- **Housing colour:** White
- **Outer diameter (mm):** 190
- **Built-in diameter (mm):** 160 - 170
- **Connection type:** Plug
- **Degree of protection (IP), front side:** IP44

**Technical specifications:**

| | |
|---|---|
| Product Name | Refl downl \|\| white \| Ø190mm \| 60° \| 3000K \| 6~15W \| EU plug |
| Ean | 8714984947900 |
| Outer box qty | 12st |
| Lamp type | LED not exchangeable |
| Lamp holder | None |
| Housing colour | White |
| Housing material | Aluminium |
| Material cover | Glass transparent |
| Connection type | EU plug |
| Height/depth | 75mm |
| Outer diameter | 190mm |
| Built-in length | - - -mm |
| Built-in width | - - -mm |
| Built-in height | 75 - -mm |
| Built-in diameter | 160 - 170mm |

17.11.2026 - Disclaimer: information subject to change.

| | |
|---|---|
| Suitable for built-in mounting | Yes |
| Suitable for surface mounting | No |
| Suitable for pedestal/floor mounting | No |
| Suitable for wall mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for light-track mounting | No |
| Suitable for clamp-mounting | Yes |
| With movement sensor | No |
| With presence detector | No |
| With light sensor | No |
| Colour of light | White |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour of light adjustable | No |
| Reflector colour | Silver |
| Colour temperature | 3000K |
| Colour rendering index CRI | 80-89 |
| Luminous flux adjustable | No |
| Light outlet | Direct |
| Beam angle | 41-80° - Wide beam |
| Beam angle adjustable | No |
| Voltage type | AC |
| Nominal voltage | 220 - 240V |
| Nominal current | 150 - 360mA |
| Number of poles | 2 |
| Light distributor | Reflector |
| Light distribution | Symmetric |
| Connectable conductor cross section | 0.75 - 2.5mm² |

17.11.2026 - Disclaimer: information subject to change.

| | |
|---|---|
| Type of control gear | LED operating device current-controlled |
| Exchangeable control gear | No |
| With control gear | Yes |
| Degree of protection (IP), front side | IP44 |
| Degree of protection (IP), rear side | IP20 |
| Surface protection | Powder coating |
| Impact strength | IK02 |
| Rated lifetime L70/B50 at 25 °C | 50000h |
| Max. system power | 15W |
| Rated luminous flux according to IEC 62722-2- 1 | 600 - 1500lm |
| Luminaire efficacy | 100 - 100lm/W |
| Power factor | 0.9 |
| Suitable for lamp power | 0 - 0W |
| Dimming method | Non-dimmable |
| Surface brushed | No |
| Type of wiring | Ending |
| Emergency power supply system | None |
| Emergency function monitoring system | None |
| Adjustability | not adjustable |
| Reflector | High-gloss |
| Warranty | 5 years |
| Ambient temperature | -20 - 45°C |
| UGR level (Unified Glare Rating) | = 16 |


17.11.2026 - Disclaimer: information subject to change.













17.11.2026 - Disclaimer: information subject to change.