Refl downl|| white | Ø225mm | 60° | 3000K | 18~30W | EU plug

ARTICLE NUMBER: 136-355

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

This downlight offers aesthetics and functionality. Its adjustable output and wide beam angle of 60° ensure optimal light distribution. A glass in front of the reflector keeps out moisture and dust, ideal for situations requiring a robust solution.

Key product features:

- **Max. system power (W):** 18 – 30
- **Colour temperature (K):** 3000
- **Housing colour:** White
- **Outer diameter (mm):** 225
- **Built-in diameter (mm):** 196 - 215
- **Connection type:** Plug
- **Degree of protection (IP), front side:** IP44

Technical specifications:

Product Name	Refl downl|| white | Ø225mm | 60° | 3000K | 18~30W | EU plug
Ean	8714984947955
Outer box qty	12st
Lamp type	LED not exchangeable
Lamp holder	None
Housing colour	White
Housing material	Aluminium
Material cover	Glass transparent
Connection type	EU plug
Outer diameter	225mm
Built-in length	- - -mm
Built-in width	- - -mm
Built-in height	87 - -mm
Built-in diameter	196 - 215mm
Suitable for built-in mounting	Yes

17.11.2026 - Disclaimer: information subject to change.

Suitable for surface mounting	No
Suitable for pedestal/floor mounting	No
Suitable for wall mounting	No
Suitable for ceiling mounting	Yes
Suitable for light-track mounting	No
Suitable for clamp-mounting	Yes
With movement sensor	No
With presence detector	No
With light sensor	No
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Colour of light adjustable	No
Reflector colour	Silver
Colour temperature	3000K
Colour rendering index CRI	80-89
Luminous flux adjustable	No
Light outlet	Direct
Beam angle	41-80° - Wide beam
Beam angle adjustable	No
Voltage type	AC
Nominal voltage	220 - 240V
Nominal current	450 - 750mA
Number of poles	2
Light distributor	Reflector
Light distribution	Symmetric
Connectable conductor cross section	0.75 - 2.5mm²
Type of control gear	LED operating device current-controlled

17.11.2026 - Disclaimer: information subject to change.


Exchangeable control gear	No
With control gear	Yes
Degree of protection (IP), front side	IP44
Degree of protection (IP), rear side	IP20
Surface protection	Powder coating
Impact strength	IK02
Rated lifetime L70/B50 at 25 °C	50000h
Max. system power	30W
Rated luminous flux according to IEC 62722-2- 1	600 - 3000lm
Luminaire efficacy	100 - 100lm/W
Power factor	0.9
Suitable for lamp power	0 - 0W
Dimming method	Non-dimmable
Surface brushed	No
Type of wiring	Ending
Emergency power supply system	None
Emergency function monitoring system	None
Adjustability	not adjustable
Reflector	High-gloss
Warranty	5 years
Ambient temperature	-20 - 45°C
UGR level (Unified Glare Rating)	= 16


17.11.2026 - Disclaimer: information subject to change.











17.11.2026 - Disclaimer: information subject to change.