Reflector downlight eco || black | Ø145mm | 10/15W | 3-CCT

ARTICLE NUMBER: 136-196

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

This reflector downlight provides glare-free lighting with a low viewing angle and UGR rating. Features a 3-CCT switch (3000K, 4000K, 6000K) and adjustable Max. system power (70%/100%). Comes with a driver and plug for fast installation.

Key product features:

- **Max. system power (W):** 10 - 15
- **Colour temperature (K):** 3000 - 6000
- **Reflector:** High-gloss
- **Housing colour:** Black
- **Outer diameter (mm):** 145
- **Built-in diameter (mm):** 120 - 140
- **Connection type:** Plug

Technical specifications:

Product Name	Reflector downlight eco || black | Ø145mm | 10/15W | 3-CCT
Ean	8714984938991
Outer box qty	30st
Lamp type	LED not exchangeable
Lamp holder	None
Housing colour	Black
Housing material	Aluminium
Material cover	Plastic, transparent
Connection type	EU plug
Height/depth	81.8mm
Outer diameter	145mm
Built-in length	- - -mm
Built-in width	- - -mm
Built-in height	81.8 - -mm
Built-in diameter	120 - 140mm

17.11.2026 - Disclaimer: information subject to change.

Suitable for built-in mounting	Yes
Suitable for surface mounting	No
Suitable for pedestal/floor mounting	No
Suitable for wall mounting	No
Suitable for ceiling mounting	Yes
Suitable for light-track mounting	No
Suitable for clamp-mounting	Yes
With movement sensor	No
With presence detector	No
With light sensor	No
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM6
Colour of light adjustable	Positions
Reflector colour	Silver
Colour temperature	3000 - 4000 - 5700K
Colour rendering index CRI	80-89
Luminous flux adjustable	No
Light outlet	Direct
Beam angle	41-80° - Wide beam
Beam angle adjustable	No
Voltage type	AC
Nominal voltage	220 - 240V
Nominal current	60 - 60mA
Number of poles	2
Light distributor	Reflector
Light distribution	Symmetric
Connectable conductor cross section	0.75 - 2.5mm²


17.11.2026 - Disclaimer: information subject to change.


Type of control gear	LED operating device current-controlled
Exchangeable control gear	No
With control gear	Yes
Degree of protection (IP), front side	IP44
Degree of protection (IP), rear side	IP20
Surface protection	Powder coating
Impact strength	IK02
Rated lifetime L70/B50 at 25 °C	50000h
Max. system power	15W
Rated luminous flux according to IEC 62722-2- 1	1000 - 1500lm
Luminaire efficacy	100 - 100lm/W
Power factor	0.96
Suitable for lamp power	0 - 0W
Dimming method	Non-dimmable
Surface brushed	No
Type of wiring	Ending
Emergency power supply system	None
Emergency function monitoring system	None
Adjustability	not adjustable
Reflector	High-gloss
Warranty	5 years
Ambient temperature	-20 - 40°C
UGR level (Unified Glare Rating)	= 22

17.11.2026 - Disclaimer: information subject to change.









17.11.2026 - Disclaimer: information subject to change.