TRONIX guided by light

Sensor connect | sensor | motion | white | surface mounted

ARTICLE NUMBER: 213-540

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

Ultra-thin radar motion sensor for the Easy Connect system. Detects movement through wood, plastic or glass and automatically switches LED lighting on or off. Suitable for cabinet and furniture lighting and other discreet interior applications.


Key product features

- **Mounting method:** Recessed
- **Max. reach frontally (m):** 5
- **Response value sensitivity adjustable:** Yes
- **Response value luminosity adjustable:** No
- **Max. duty cycle (min):** 5
- **With movement sensor:** Yes
- **With light sensor:** No

Technical specifications:

Product Name	Sensor connect | sensor | motion | white | surface mounted
Ean	8714984954090
Outer box qty	1st
Colour	White
Type	Movement sensor
Material	Plastic
Material quality	Thermoplastic
Sensor connect	Yes
Mounting method	Flush-mounted
Mounting height	5m
Suitable for degree of protection (IP)	IP20
Suitable for wireless transmission	No
Constant light control	No
Networkable	No

Max. reach sideways	5m
Max. reach frontally	5m
Detection angle horizontal	120 - 120??
Min. switch-on time	10s
Max. duty cycle	5min
With presence detector	No
With movement sensor	Yes
With light sensor	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	No
Teach-function for response value luminosity	No
Dim function with dimmer basic element	No
Switch-off delay self-learning	No
Operation mode switch	No
Staircase light controller	No
Halogen free	Yes
RAL-number (similar)	9016
Surface finishing	Matt
Warranty	5 years
Dimming D4i	No


52.00mm
7.00mm