TRONIX guided by light

Sensor motion for UFO high bay 190Lm/W

ARTICLE NUMBER: 950-115

View this product in our webshop



17.11.2026 - Disclaimer: information subject to change.

This sensor has been specially developed for the Tronix UFO high bay 190 Lm/W collection. Using this sensor, it is possible to create the ideal high bay. This can be done using different methods, such as time, lux value or sensitivity.

To access everything this sensor has to offer, remote control 950-116 is required.

Features

- Choice of detection methods: Sensitivity (motion), lux value (daylight), time and operation time
- Ability to dim the light of the high bay, possibly after a certain amount of time
- Fully adjustable using remote control 950-116
- Quick installation: loosen the cap under the high bay, insert the sensor and turn it a quarter turn

Technical specifications:

Product Name	Sensor motion for UFO high bay 190Lm/W
Ean	8714984943537
Outer box qty	1st
Colour	White
Material	Plastic
Material quality	Thermoplastic
Sensor connect	No
Mounting method	Other
Mounting height	15m
Suitable for degree of protection (IP)	IP65
Suitable for wireless transmission	No
Constant light control	No
Networkable	No

Max. reach sideways	12m
Max. reach frontally	20m
Diameter reach on floor	12m
Detection angle horizontal	30 - 150??
Min. switch-on time	5s
Max. duty cycle	30min
With presence detector	No
With movement sensor	Yes
With light sensor	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	No
Teach-function for response value luminosity	No
Dim function with dimmer basic element	Yes
Switch-off delay self-learning	Yes
Operation mode switch	No
Staircase light controller	No
Halogen free	Yes
RAL-number (similar)	9016
Surface finishing	Matt
Warranty	5 years
Dimming D4i	No

17.11.2026 - Disclaimer: information subject to change.