# Zigbee | driver | 25W | 250~700mA | max. 54V | NFC

ARTICLE NUMBER: 214-261

View this product in our webshop

zigbee




17.11.2026 - Disclaimer: information subject to change.

Zigbee 3.0 LED driver for constant current applications up to 25 W. Output current adjustable via NFC. Compatible with Philips Hue, Homey and other platforms.

**Key product features**

- **Suitable for constant current:** Yes
- **Output voltage (V):** 6 – 54
- **Output current (mA):** 250 – 700
- **Output power (W):** 1.5 – 25
- **Input voltage (V):** 200 – 240
- **Control protocol:** Zigbee
- **Control type:** Constant current

**Technical specifications:**


| | |
|---|---|
| Product Name | Zigbee \| driver \| 25W \| 250~700mA \| max. 54V \| NFC |
| Ean | 8714984948358 |
| Outer box qty | 1st |
| Housing | Plastic housing |
| Model | Static |
| Output voltage | 6 - 54V |
| Output current | 250 - 700mA |
| Suitable for outdoor use | No |
| Suitable for DC-voltage (primary side) | Yes |
| Output power | 1.5 - 25W |
| Degree of protection (IP) | IP20 |
| Length | 120mm |
| Width | 41mm |
| Height | 28mm |
| Power consumption | 25W |

17.11.2026 - Disclaimer: information subject to change.

| | |
|---|---|
| Input voltage | 200 - 240V |
| Frequency input voltage | 50 - 60Hz |
| Overload protection | Yes |
| Overtemperature protection | Yes |
| Control method | Zigbee |
| Short-circuit protected | Yes |
| Ambient temperature | -25 - 45??C |
| Driver lifetime | 100000h |
| DIN-rail mounting | No |
| Brand | Tronix Lighting |
| Dimmable | Yes |
| Emergency power supply system | Central (central battery) |
| Control type | Constant current |
| Warranty | 5 years |

17.11.2026 - Disclaimer: information subject to change.




17.11.2026 - Disclaimer: information subject to change.